# NASA/TM-2000-209891, Vol. 21



# Technical Report Series on the Boreal Ecosystem-Atmosphere Study (BOREAS)

Forrest G. Hall and David E. Knapp, Editors

# Volume 21 BOREAS HYD-2 Estimated Snow Water Equivalent (SWE) from Microwave Measurements

H. Powell and A.T.C. Chang

National Aeronautics and Space Administration

**Goddard Space Flight Center** Greenbelt, Maryland 20771

#### The NASA STI Program Office ... in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- TECHNICAL PUBLICATION. Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- TECHNICAL MEMORANDUM. Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- CONTRACTOR REPORT. Scientific and technical findings by NASA-sponsored contractors and grantees.

- CONFERENCE PUBLICATION. Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- SPECIAL PUBLICATION. Scientific, technical, or historical information from NASA programs, projects, and mission, often concerned with subjects having substantial public interest.
- TECHNICAL TRANSLATION.
   English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at http://www.sti.nasa.gov/STI-homepage.html
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA Access Help Desk at (301) 621-0134
- Telephone the NASA Access Help Desk at (301) 621-0390
- Write to:
   NASA Access Help Desk
   NASA Center for AeroSpace Information
   7121 Standard Drive

Hanover, MD 21076-1320

# NASA/TM-2000-209891, Vol. 21



# Technical Report Series on the Boreal Ecosystem-Atmosphere Study (BOREAS)

Forrest G. Hall and David E. Knapp, Editors

# Volume 21 BOREAS HYD-2 Estimated Snow Water Equivalent (SWE) from Microwave Measurements

Hugh Powell and Alfred T.C. Chang Goddard Space Flight Center

National Aeronautics and Space Administration

**Goddard Space Flight Center** Greenbelt, Maryland 20771

	Available from:	
NIAGA Conton for A G T C		Ni-diamater distribution of the control of the cont
NASA Center for AeroSpace Information		National Technical Information Service
7121 Standard Drive		5285 Port Royal Road
Hanover, MD 21076-1320		Springfield, VA 22161
Drice Code: A17		Del - C 1 - A 10
Price Code: A17		Price Code: A10

# BOREAS HYD-2 Estimated Snow Water Equivalent (SWE) from Microwave Measurements

Hugh Powell, Alfred T. C. Chang

## **Summary**

The surface meteorological data collected at the BOREAS tower and ancillary sites are being used as inputs to an energy balance model to monitor the amount of snow storage in the boreal forest region. The BOREAS HYD-2 team used SWE derived from an energy balance model and in situ observed SWE to compare the SWE inferred from airborne and spaceborne microwave data, and to assess the accuracy of microwave retrieval algorithms. The major external measurements that are needed are snowpack temperature profiles, in situ snow areal extent, and SWE data. The data in this data set were collected during February 1994 and cover portions of the SSA, NSA, and the transect areas. The data are available from BORIS as comma-delimited tabular ASCII files.

#### **Table of Contents**

- 1) Data Set Overview
- 2) Investigator(s)
- 3) Theory of Measurements
- 4) Equipment
- 5) Data Acquisition Methods
- 6) Observations
- 7) Data Description
- 8) Data Organization
- 9) Data Manipulations
- 10) Errors
- 11) Notes
- 12) Application of the Data Set
- 13) Future Modifications and Plans
- 14) Software
- 15) Data Access
- 16) Output Products and Availability
- 17) References
- 18) Glossary of Terms
- 19) List of Acronyms
- 20) Document Information

#### 1. Data Set Overview

#### 1.1 Data Set Identification

BOREAS HYD-02 Estimated Snow Water Equivalent (SWE) from Microwave Measurements

#### 1.2 Data Set Introduction

The estimated Snow Water Equivalent (SWE) data set contains SWE as obtained via airborne measurements. The time period of the experiment was 02-Feb to 18-Feb-1994 during the BOReal Ecosystem-Atmosphere Study (BOREAS) winter focused field campaign (FFC-W). The instrumentation used was a series of microwave radiometers (specifically the 18-, 37-, and 92-GHz channels) that were mounted on a Twin Otter aircraft. The data set also contains other relevant data regarding the conditions under which each measurement was taken. For example, the temperature and dewpoint at the time of the measurement as well as the pitch and roll of the aircraft are also included.

#### 1.3 Objective/Purpose

The objective of this investigation was to quantify the storage of water in snowpacks beneath the forest canopy. Ground water measurements were used as validation for the airborne and spaceborne SWE algorithm. This data set was created based on airborne microwave measurements to help address the question of the extent to which differences in surface cover affect snow storage.

#### 1.4 Summary of Parameters

The specific parameters under observation for this experiment are the snowpack temperature profiles, the snow areal extent, and the SWE measured.

#### 1.5 Discussion

During the 1994 FFC-W, 14 Twin Otter flights were made for the BOREAS project. Each of the 14 flights represents a number of different flight lines. The latitude and longitude of each data record are included with the data. Three microwave radiometers (18-, 37-, and 92-GHz) were mounted onboard the aircraft, in addition to videocameras and a PRT-5 thermal sensor. SWE was derived from the microwave radiometer data that were collected.

#### 1.6 Related Data Sets

Nimbus-7 SMMR derived global snow depth maps (available through the National Snow and Ice Data Center (NSIDC), http://www-nsidc.colorado.edu/NASA/GUIDE/ [Internet Link]).

BOREAS HYD-03 Snow Depths Data

BOREAS HYD-03 Snow PitsData

BOREAS HYD-03 Snow Temperature DataA HREF="../hyd03/hyd03\_snow\_depths.html">

BOREAS HYD-03 Snow Water Data

BOREAS HYD-04 Areal Snow Course Data

BOREAS HYD-04 Standard Snow Course Data

# 2. Investigator(s)

#### 2.1 Investigator(s) Name and Title

#### **Principal Investigator:**

Dr. Alfred T.C. Chang NASA GSFC Hydrological Sciences Branch

#### **Co-Investigators:**

Dr. Dorothy K. Hall NASA GSFC Hydrological Sciences Branch

Dr. James L. Foster NASA GSFC Hydrological Sciences Branch

#### 2.2 Title of Investigation

Validation of a Passive Microwave Snow Water Equivalent Algorithm Using an Energy Balance Model

#### 2.3 Contact Information

#### **Contact 1:**

Mr. Hugh Powell NASA GSFC Code 974 Greenbelt, MD 20771 (301) 286-2310 Hugh.Powell.1@gsfc.nasa.gov

#### Contact 2:

Dr. Alfred T. C. Chang NASA GSFC Code 974 Greenbelt, MD 20771 (301) 286-8997 Alfred.T.Chang.1@gsfc.nasa.gov

#### **Contact 3:**

David Knapp Raytheon ITSS NASA GSFC Code 923 Greenbelt, MD 20771 (301) 286-1424 (301) 286-0239 (fax) David.Knapp@gsfc.nasa.gov

# 3. Theory of Measurements

Microwave signatures have been used to infer SWE values over Canadian Prairie with some success (Goodison and Walker, 1993). Microwave radiation emanates from features on or near the surface of Earth at an intensity that is proportional to the product of the physical temperature and the emissivity of the surface. The measured value, referred to as the brightness temperature (TB), can simply be expressed as:

$$TB = (R * T_{sky} + (1 - R) * T_{surf}e-t + T_{atm})$$
 (1)

where e-t is the atmospheric transmissivity, R is the surface reflectivity, T<SUB>sky</SUB> is the sky radiation, T<SUB>surf</SUB> is the surface emission, and T<SUB>atm</SUB> is the emission from the intervening atmosphere. In the microwave region, both T<SUB>sky</SUB> and T<SUB> are small and can be neglected. Thus, the observed TB is directly related to surface features.

Based on radiative transfer calculations (Chang et al., 1987), a relationship between brightness temperature and the number of snow crystals was developed for SWE retrieval. The differences between the 18- and 37-GHz horizontal polarization brightness temperature are linearly related to the SWE values when SWE is less than 200 mm. The scattering information comes largely from the 37-GHz signal. The 18-GHz signal serves as the background reference. The SWE - brightness temperature relationship of a homogeneous snow layer with crystals having a mean radius of 0.3 mm and density of 300 kg/m³ for the Scanning Multichannel Microwave Radiometer (SMMR) data can be expressed as follows (Chang et al., 1987);

$$SWE = 4.8 \times (T18H - T37H)$$
 (2)

where SWE is the snow water equivalent in mm of equivalent water, and T18H and T37H are the brightness temperatures for the 18- and 37-GHz horizontal polarizations, respectively. Both vertical and horizontal polarization will give generally similar results in Eq. (2). Because of the differences in the surface snow characteristics, researchers have used either vertical or horizontal polarization (Hallikainen and Jolma, 1992; Goodison and Walker, 1994) in retrieving the SWE. Rott and Aschbacher (1989) proposed a more generalized relationship of SWE and brightness temperature:

$$SWE = A + B * DTB$$
 (3)

where A and B are the offset and slope for brightness temperature difference and DTB is the brightness temperature difference between a high-scattering channel (37- or 85-GHz) and a low-scattering channel (18- or 19-GHz) for vertical or horizontal polarization channels. Based on ground measurements of SWE in forests, A and B were determined for the airborne sensor in the boreal region. For this experiment, A and B are 0.0 and 1.7, respectively, when using the 18- and 37-GHz vertical polarization data.

The brightness temperature difference for forest-covered areas will cancel out if the emissivities of forest for both the high-scattering and the low-scattering channels are approximately the same. This is based on the findings that the emissivities for forest in Finland at 37 and 18 GHz are very similar and have the values of 0.9 to 0.92 (Hallikainen et al., 1988). Thus, only the snow-covered fraction contributes to the brightness temperature difference. For a footprint with a fraction of forest cover (f) and fraction snow cover (1 -f), Eq. (3) will become

SWE = 
$$1.7 * DTB / (1 - f)$$
 (4)

Over the forested pixels, Eq. (3) would underestimate the SWE if not corrected for the forest cover. The amount of underestimation depends on the fraction of forest cover in Eq. (4). This equation was derived by Hallikainen for boreal forests in Finland that have similar forest conditions as the BOREAS sites. Because of the low sun angles for early February in the BOREAS test sites, accurate forest cover determination is difficult to obtain from the video. Therefore, fractional forest cover corrections were not included in this data set and f was set equal to 0. Data users may compute an estimate of the fractional forest cover from other BOREAS data sources and apply Eq. (4) to correct for the forest cover.

# 4. Equipment

#### 4.1 Sensor/Instrument Description

Three dual polarization microwave radiometers at 18, 37, and 92 GHz were mounted onto a Canadian Twin Otter aircraft. Thermal radiation in the microwave region was measured using Dicke-type radiometers with two reference sources in 18, 37, and 92 GHz. The microwave radiation was received by square wave detectors. A PRT-5 infrared (IR) radiometer was also mounted on the aircraft.

#### 4.1.1 Collection Environment

The data were collected during the BOREAS experiment FFC-W, which occurred from 02-Feb to 18-Feb-1994. The areas over which the data were collected included the BOREAS Northern Study Area (NSA), BOREAS Southern Study Area (SSA), and other surrounding areas. There were 14 flyovers for this particular investigation.

#### 4.1.2 Source/Platform

Radiometers were mounted on the right side of the Twin Otter aircraft with a 45-degree look-angle.

#### 4.1.3 Source/Platform Mission Objective

The mission of the Twin Otter was to serve as a platform for the brightness temperature measurements.

#### 4.1.4 Key Variables

Brightness temperatures, IR temperature, and aircraft locations.

#### 4.1.5 Principles of Operation

Dicke-type radiometers with two reference sources were used to measure brightness temperature. The 18-, 37-, and 92-GHz were Dicke radiometers (Ulaby et al., 1981). It was basically a total-power radiometer with (1) Dicke switch connected at the receiver input and used to modulate the input signal, and (2) a synchronous demodulator placed between the square-law detector and the low-pass filter. The predetection section consisted of the radio frequency (RF) amplifier, mixer, and intermediate frequency (IF) amplifier. It operated like a super-heterodyne radio receiver.

To stabilize the gain of the receiver, two internal microwave references were used, a warm load and a cold load, respectively. The warm loads were the ambient temperatures of the instrument, about 285 K. A noise diode was used as a cold load for the 18- and 37-GHz radiometers. For the 92-GHz radiometer, outside air was used to cool the cold load to about 240 K. Thus, the dynamic range of the 92-GHz radiometer is not optimum.

#### 4.1.6 Instrument Measurement Geometry

The radiometers were set up such that a 45-degree angle looking out of the aircraft to the right was achieved. The pitch and roll of the aircraft were also recorded.

#### 4.1.7 Manufacturer of Instrument

The radiometers were assembled at Goddard Space Flight Center (GSFC) using commercial parts. An Intel 486 IBM-compatible personal computer (PC) was used as the data logger.

#### 4.2 Calibration

For the Dicke radiometer, a warm and a cold reference load are used to stabilize the gain. These international calibration load readings were taken once each minute. During the calibration cycle, no scene data were taken. External calibrations were performed by aiming the radiometer to known brightness temperature targets. Liquid nitrogen (77 K) and ambient Ecosorb target (290 K) were used as references. These calibrations were performed on the ground, while the instruments were mounted on the Twin Otter aircraft, before, during, and after the flight mission. Before and after shipping the instrument package, external calibrations were also done at GSFC. These calibrations were performed to make sure that there was no drift of the instrument during the BOREAS experiment.

#### 4.2.1 Specifications

Radiometers were calibrated with clear sky, liquid nitrogen, and warm ecosorb targets.

#### 4.2.1.1 Tolerance

Accuracy of the radiometers is about 2 K in nominal temperature range.

#### 4.2.2 Frequency of Calibration

During a flight, calibration was done for 6 seconds out of every minute of data recording. External calibration was done twice during the mission.

#### 4.2.3 Other Calibration Information

Losses for each component were measured in the laboratory in 1992.

# 5. Data Acquisition Methods

Microwave brightness temperatures were taken by aircraft from takeoff to landing, nominally lasting about 2 hours. Data were collected in 1-minute blocks, which included 6 seconds of calibration and 54 seconds of data from target. Data were recorded on the hard disk of a PC and were copied to other computers for further processing.

#### 6. Observations

#### 6.1 Data Notes

At the beginning of February 1994, the temperatures were very cold (about -40 °C), and the snowpack should have been dry. The temperature warmed up slowly during the 2 weeks of experimentation. During Flight 14, the air temperatures were close to 0 °C; thus, surface melting was possible. Data were taken over the NSA and SSA sites during the winter FFC.

#### **6.2 Field Notes**

None.

# 7. Data Description

#### 7.1 Spatial Characteristics

#### 7.1.1 Spatial Coverage

Data were taken over the BOREAS NSA, SSA, and transect areas. The North American Datum of 1983 (NAD83) coordinates of the areas are:

NSA

Corner	Longitude	Latitude
Northwest	98.82° W	56.247° N
Northeast	97.24° W	56.081° N
Southeast	97.49° W	55.377° N
Southwest	99.05° W	55.540° N
SSA		
Corner	Longitude	Latitude
Northwest	106.23° W	54.319° N
Northeast	104.24° W	54.223° N
Southeast	104.37° W	53.419° N
Southwest	106.30° W	53.513° N

The following table indicates the study area at which data were collected. 'REGION' indicates that the data were not collected in the SSA, NSA, nor in the area in between; the data for this flight were likely collected south of the SSA, in an agricultural area. 'TRANSECT' indicates that the data were collected in the transect area between the NSA and SSA.

SPATIAL_COVERAGE	DATE_OBS	START_TIME	END_TIME	FLIGHT_NUM
SSA	06-FEB-1994	1527	1723	FLIGHT #1
REGION	06-FEB-1994	1808	1942	FLIGHT #2
SSA	06-FEB-1994	2018	2237	FLIGHT #3
SSA	07-FEB-1994	1537	1758	FLIGHT #4
SSA	07-FEB-1994	1943	2134	FLIGHT #5
SSA	08-FEB-1994	1456	1621	FLIGHT #6
TRANSECT	08-FEB-1994	1834	2006	FLIGHT #7
NSA	08-FEB-1994	2049	2213	FLIGHT #8
NSA	09-FEB-1994	1558	1806	FLIGHT #9
NSA	09-FEB-1994	1856	2012	FLIGHT #10
SSA	09-FEB-1994	2057	2238	FLIGHT #11
SSA	10-FEB-1994	1957	2218	FLIGHT #12
SSA	11-FEB-1994	2040	2308	FLIGHT #13
SSA	13-FEB-1994	1957	2221	FLIGHT #14

#### 7.1.2 Spatial Coverage Map

Not available.

#### 7.1.3 Spatial Resolution

These data were taken from an aircraft altitude of 2,500 feet, which resulted in a spatial resolution of approximately 350 feet at the 45-degree viewing angle. The spatial resolution of a microwave radiometer depends on the beam width of the antenna. The beam width of the antenna is 6°, which is roughly about one tenth of a radian. Thus, the field of view (FOV) is about one tenth of the aircraft altitude. Normally, the radiometers were looking at 45° to the left side of the aircraft. When the aircraft pitches or rolls, the FOV size and position could be changed greatly. Data with large pitch and roll angles should not be used for SWE study.

# 7.1.4 Projection

Not applicable.

#### 7.1.5 Grid Description

Not applicable.

#### 7.2 Temporal Characteristics

Most of the 14 flight lines were covered once during the mission.

#### 7.2.1 Temporal Coverage

The data were collected from 06-Feb-1994 to 13-Feb-1994.

#### 7.2.2 Temporal Coverage Map

Not available.

#### 7.2.3 Temporal Resolution

In each minute, data values were collected once per second for 53 seconds; the remaining time was used for instrument calibration. Some data gaps exist.

#### 7.3 Data Characteristics

#### 7.3.1 Parameter/Variable

The data contained in the data files are:

Parameter -----GMT 18V 18H 37V 37H 92V 92H SWE Evet Ralt PsAlt AcLat AcLong FltLat FltLong TAS GS Hdq Wind Temp DewP PRT5 Sun Ptch Roll DX DY

# 7.3.2 Variable Description/Definition

The descriptions of the parameters in the data files are:

Parameter	Definition			
GMT	Greenwich mean time			
18V	18 GHz brightness temperature (V)			
18H	18 GHz brightness temperature (H)			
37V	37 GHz brightness temperature (V)			
37H	37 GHz brightness temperature (H)			
92V	92 GHz brightness temperature (V)			
92H	92 GHz brightness temperature (H)			
SWE	Estimated snow water equivalent			
Evet	Flight line marker			
Ralt	Radar Altitude			
PsAlt	Pressure Altitude			
AcLat	Latitude of aircraft			
AcLong	Longitude of aircraft			
FltLat	Latitude of measurement location			

FltLong Longitude of measurement location
TAS True air speed
GS Ground speed
Hdg Aircraft heading
Wind Wind direction and speed
Temp Air temperature
DewP Dewpoint temperature
PRT5 IR surface temperature
Sun Solar input
Ptch Aircraft Pitch angle
Roll Aircraft Roll angle
DX x offset
DY y offset

#### 7.3.3 Unit of Measurement

The descriptions of the units in the data files are:

Parameter	Units
GMT	[Hr:Min:Sec]
18V	[Kelvin]
18H	[Kelvin]
37V	[Kelvin]
37H	[Kelvin]
92V	[Kelvin]
92H	[Kelvin]
SWE	[millimeters]
Evet	[None]
Ralt	[meters]
PsAlt	[meters]
AcLat	[degrees of latitude]
AcLong	[degrees of longitude]
FltLat	[degrees of latitude]
FltLong	[degrees of longitude]
TAS	[meters][second^-1]
GS	[meters][second^-1]
Hdg	[degrees]
Wind	[degrees][meters][second^-1]
Temp	[degrees Celsius]
DewP	[degrees Celsius]
PRT5	[degrees Celsius]
Sun	[Watts][meter^-2]
Ptch	[degrees]
Roll	[degrees]
DX	[meters]
DY	[meters]

# 7.3.4 Data Source

The descriptions of the source of the data files are:

Parameter	Source
GMT	WWV radio station
18V	radiometer
18H	radiometer
37V	radiometer
37H	radiometer
92V	radiometer
92H	radiometer
SWE	inferred
Evet	1 flight line
	0 non-flight line
Ralt	radar
PsAlt	Barometer
AcLat	GPS
AcLong	GPS
FltLat	GPS
FltLong	GPS
TAS	INS
GS	INS
Hdg	INS
Wind	INS
Temp	Rosemount
DewP	Hygrometer
PRT5	Barnes PRT5
Sun	Pyrometer
Ptch	INS
Roll	INS
DX	GPS
DY	GPS

**7.3.5 Data Range**The descriptions of the ranges of the data files are:

Parameter	Range
GMT	00:00:00 - 23:59:59 hours
18V	0-300
18H	0-300
37V	0-300
37H	0-300
92V	0-300
92H	0-300
SWE	0-250 mm
Evet	0-1
Ralt	None given.
PsAlt	None given.
AcLat	None given.
AcLong	None given.
FltLat	None given.
FltLong	None given.

```
TAS
            0 - 150
GS
           0 - 150
Hdq
           0-360
Wind Dir. 0-360
Wind Sp.
           0-200
           None given.
Temp
           None given.
DewP
           None given.
PRT5
           None given.
Sun
           -90 to 90
Ptch
Roll
            -90 to 90
           None given.
DX
DY
           None given.
```

#### 7.4 Sample Data Record

The following are wrapped versions of sample data records from one of the data files:

```
GMT, AMMR 18-V, AMMR 18-H, AMMR 37-V, AMMR 37-H, AMMR 92-V, AMMR 92-H, SWE, Evnt, RadAlt(m), PsAlt(m), AcLat(Deg), AcLon(Deg), FtpLat(Deg), FtpLon(Deg), AirSpd(m/s), GrSpd(m/s), Hdg(Deg), WinDir(Deg), WinSpd(m/s), AirTemp(C), DewPt(C), PRT5(C), SolarIn(W/m2), AcPitch(Deg), AcRoll(Deg), XOff(m), YOff(m)

19:57:41,,,,,,0,2,429,53.2178,105.684,53.2178,105.684,-0.4,0.2,89,251,0.4,-2,-11.7,-15.3,297,-0.8,-0.4,0,-2

19:57:42,,,,,,0,2,429,53.2178,105.684,53.2178,105.684,-0.4,0.2,89,251,0.4,-2,-11.8,-15.3,297,-1,-0.5,0,-2

19:57:43,,,,,,0,2,429,53.2178,105.684,53.2178,105.684,-0.4,0.2,89,251,0.4,-1.9,-11.8,-15.3,297,-1.1,-0.5,0,-2
```

# 8. Data Organization

#### 8.1 Data Granularity

The smallest amount of data that can be ordered from this data set is the data from one flight.

#### 8.2 Data Format

The Compact Disk-Read-Only Memory (CD-ROM) files contain American Standard Code for Information Interchange (ASCII) numerical and character fields of varying length separated by commas. There are no spaces between the fields.

Each data file on the CD-ROM has four header lines of Hyper-Text Markup Language (HTML) code at the top. When viewed with a Web browser, this code displays header information (data set title, location, date, acknowledgments, etc.) and a series of HTML links to associated data files and related data sets. Line 5 of each data file is a list of the column names, and line 6 and following lines contain the actual data.

The SWE data set contains 28 columns of data. It is written in ASCII text with two header lines describing the contents of the column beneath it. The data columns are comma delimited. The columns in left-to-right order are:

```
GMT - Greenwich Mean Time, the time at which the observation was made 18-V - The 18-GHz vertical channel reading in Kelvin 18-H - The 18-GHz horizontal channel reading in Kelvin 37-V - The 37-GHz vertical channel reading in Kelvin 37-H - The 37-GHz horizontal channel reading in Kelvin 92-V - The 92-GHz vertical channel reading in Kelvin 92-H - The 92-GHz horizontal channel reading in Kelvin
```

SWE - Snow Water Equivalent, in mm

Evnt - Event marker, set to 1 over predetermined flight lines

RAlt - Radar altimeter reading in meters

PsAlt - Pressure altimeter reading in meters

AcLat - Recorded latitude of aircraft in degrees

AcLong - Recorded longitude of aircraft in degrees

FtpLat - Recorded latitude of footprint in degrees

FtpLong - Recorded longitude of footprint in degrees

TAS - True air speed in meters per second

GS - Ground speed in meters per second

Hdg - Recorded aircraft heading in degrees

Wind - Direction of wind in degrees

Wind - Speed of wind in meters per second

Temp - Recorded air temperature in degrees Celsius

DewP - Recorded dew point temperature in degrees Celsius

PRT5 - IR surface temperature in degrees Celsius

Sun - Solar intensity upon surface in Watts per meter squared

Ptch - Recorded aircraft pitch in degrees Roll - Recorded aircraft roll in degrees

DX - X-offset between aircraft and footprint in meters

DY - Y-offset between aircraft and footprint in meters

# 9. Data Manipulations

#### 9.1 Formulae

Measured radiometric units have been converted to brightness temperature using the following equations:

TB = TH-(dc-hc)/(cc-hc)\*(TH-TC)

where: dc = data counts

cc = cold counts

hc = hot counts

TC = cold load temperature

TH = hot load temperature

#### 9.1.1 Derivation Techniques and Algorithms

Radiometer calibration was done by pointing the antenna to cold sky and a liquid nitrogen bucket as the cold references; ecosorb at ambient temperature is used as the warm reference target.

## 9.2 Data Processing Sequence

## 9.2.1 Processing Steps

The data collected during the flights were processed using the following steps:

- The raw data counts from each radiometer were read from the collected data file.
- These data were then converted to antenna temperature using the calibration equations derived.
- Loss corrections were applied to the antenna temperature to create brightness temperature.
- SWE was derived from equations.
- SWE was merged with aircraft navigation data and PRT-5 IR data.
- Output was saved on 8-mm tape cartridge.
- BOREAS Information System (BORIS) staff read the files from tape, added commas to delimit the different columns, and wrote the data back to tape.

#### 9.2.2 Processing Changes

None.

#### 9.3 Calculations

## 9.3.1 Special Corrections/Adjustments

None given.

#### 9.3.2 Calculated Variables

Please refer to Eq. (3) in Section 3 of this document for the equation used to infer the SWE values.

#### 9.4 Graphs and Plots

Brightness temperatures for each flight are plotted as a function of time, as a quick-look product. Please contact personnel at the Hydrological Sciences Branch at GSFC.

#### 10. Errors

#### 10.1 Sources of Error

Errors in the calibrated brightness temperature data may arise from several sources:

- Instrumentation operation temperature: Because of the cold ambient temperature, the instrument temperature could not be controlled accurately.
- Stability of the noise diode.

#### 10.2 Quality Assessment

#### 10.2.1 Data Validation by Source

Comparisons were made with Special Sensor Microwave Imager (SSM/I) data over the same area and available water targets.

#### 10.2.2 Confidence Level/Accuracy Judgment

The 18- and 37-GHz radiometers are believed to be accurate to about +/-3 K. The 92-GHz radiometer may be accurate to approximately +/-10 K. For SWE value, the accuracy is approximately 5 mm.

#### **10.2.3 Measurement Error for Parameters**

None given.

#### 10.2.4 Additional Quality Assessments

None given.

#### 10.2.5 Data Verification by Data Center

None given.

#### 11. Notes

#### 11.1 Limitations of the Data

During the aircraft flights, it was found that the 92-GHz brightness temperature was not very stable because of the instability in the cold reference load temperature. There was also a problem with the 37-GHz horizontal polarization data. Therefore, the quality of these data is somewhat uncertain.

#### 11.2 Known Problems with the Data

None given.

#### 11.3 Usage Guidance

None given.

#### 11.4 Other Relevant Information

None given.

# 12. Application of the Data Set

This data set may be used to study the energy balance for the BOREAS sites.

#### 13. Future Modification and Plans

There are no reprocessing plans at this time.

#### 14. Software

#### **14.1 Software Description**

None given.

#### 14.2 Software Access

None given.

#### 15. Data Access

The SWE data are available from the Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC).

#### **15.1 Contact Information**

For BOREAS data and documentation please contact:

ORNL DAAC User Services Oak Ridge National Laboratory P.O. Box 2008 MS-6407 Oak Ridge, TN 37831-6407 Phone: (423) 241-3952

Fax: (423) 574-4665

E-mail: ornldaac@ornl.gov or ornl@eos.nasa.gov

#### 15.2 Data Center Identification

Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC) for Biogeochemical Dynamics http://www-eosdis.ornl.gov/ [Internet Link].

#### 15.3 Procedures for Obtaining Data

Users may obtain data directly through the ORNL DAAC online search and order system [http://www-eosdis.ornl.gov/] and the anonymous FTP site [ftp://www-eosdis.ornl.gov/data/] or by contacting User Services by electronic mail, telephone, fax, letter, or personal visit using the contact information in Section 15.1.

#### 15.4 Data Center Status/Plans

The ORNL DAAC is the primary source for BOREAS field measurement, image, GIS, and hardcopy data products. The BOREAS CD-ROM and data referenced or listed in inventories on the CD-ROM are available from the ORNL DAAC.

# 16. Output Products and Availability

#### **16.1 Tape Products**

The data can be made available on 8-mm tape.

#### 16.2 Film Products

None.

#### **16.3 Other Products**

These data are available on the BOREAS CD-ROM series. Videotapes from the Twin Otter flights are also available.

#### 17. References

# 17.1 Platform/Sensor/Instrument/Data Processing Documentation

None given.

#### 17.2 Journal Articles and Study Reports

Chang, A.T.C., J.L. Foster, and D.K. Hall. 1987. Nimbus-7 derived global snow cover parameters. Annals of Glaciology, 9:39-44.

Chang, A.T.C., J.L. Foster, and D.K. Hall. 1990. Effect of vegetation on microwave snow water equivalent estimates. Proceedings of the International Symposium on Remote Sensing and Water Resources, Enschede, The Netherlands, 137-145.

Chang, A.T.C., J.L. Foster, D.K. Hall, B.E. Goodison, A.E. Walker, J.R. Metcalfe, and A. Harby. 1997. Snow parameters derived from microwave measurements during the BOREAS winter field campaign. Journal of Geophysical Research, 102(D24): 29,663-29,671.

Chang, A.T.C., J.L. Foster, D.K. Hall, A.E. Walker, B.E. Goodison, and J.R. Metcalfe. 1996. Snow Parameters Derived From Microwave Measurements During the BOREAS Winter Field Campaign. 22nd Conference on Agricultural and Forest Meteorology (AMS Conference), Atlanta, GA, Jan. 1996.

Goodison, B.E. and A.E. Walker. 1993. Use of snow cover derived from satellite passive microwave data as an indicator of climate change. Annals of Glaciology, 17:137-142.

- Goodison, B.E. and A.E. Walker. 1994. Canadian development and use of snow cover information from passive microwave satellite data. Passive Microwave Remote Sensing of Land-Atmosphere Interactions, (Eds. Choudhury, Kerr, Njoku and Pampaloni), VSP, 245-262.
- Goodison, B., A.E. Walker, and F.W. Thirkettle. 1990. Determination of snowcover on the Canadian prairies using passive microwave data. Proceedings for the International Symposium on Remote Sensing and Water Resources, Enschede, The Netherlands, 127-136.
- Hall, D.K., J.L. Foster, and A.T.C. Chang. 1994. Mapping snow cover during the BOREAS Winter Experiment, AGU Annual Fall Meeting.
- Hallikainen, M.T. and P.A. Jolma. 1992. Comparison of algorithms for retrieval of snow water equivalent from Nimbus-7 SMMR data in Finland. IEEE Trans. on Geoscience and Remote Sensing, 30: 124-131.
- Hallikainen, M.T., P.A. Jolma, and J.M. Hyyppa. 1988. Satellite microwave radiometry of forest and surface types in Finland. IEEE Trans. on Geoscience and Remote Sensing, 26:622-628.
- Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. 2000. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM.
- Rott, H. and J. Aschbacher. 1989. On the use of satellite microwave radiometers for large-scale hydrology, Proc. IASH 3rd Int. Assembly on Remote Sensing and large Scale Global Processes, Baltimore, 21-30.
- Sellers, P. and F. Hall. 1994. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1994-3.0, NASA BOREAS Report (EXPLAN 94).
- Sellers, P. and F. Hall. 1996. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1996-2.0, NASA BOREAS Report (EXPLAN 96).
- Sellers, P., F. Hall, and K.F. Huemmrich. 1996. Boreal Ecosystem-Atmosphere Study: 1994 Operations. NASA BOREAS Report (OPS DOC 94).
- Sellers, P., F. Hall, and K.F. Huemmrich. 1997. Boreal Ecosystem-Atmosphere Study: 1996 Operations. NASA BOREAS Report (OPS DOC 96).
- Sellers, P., F. Hall, H. Margolis, B. Kelly, D. Baldocchi, G. den Hartog, J. Cihlar, M.G. Ryan, B. Goodison, P. Crill, K.J. Ranson, D. Lettenmaier, and D.E. Wickland. 1995. The boreal ecosystem-atmosphere study (BOREAS): an overview and early results from the 1994 field year. Bulletin of the American Meteorological Society. 76(9):1549-1577.
- Sellers, P.J., F.G. Hall, R.D. Kelly, A. Black, D. Baldocchi, J. Berry, M. Ryan, K.J. Ranson, P.M. Crill, D.P. Lettenmaier, H. Margolis, J. Cihlar, J. Newcomer, D. Fitzjarrald, P.G. Jarvis, S.T. Gower, D. Halliwell, D. Williams, B. Goodison, D.E. Wickland, and F.E. Guertin. 1997. BOREAS in 1997: Experiment Overview, Scientific Results and Future Directions. Journal of Geophysical Research 102(D24): 28,731-28,770.
- Ulaby, F.T., R.K. Moore, and A.K. Fung. 1981. Microwave Remote Sensing, Active and passive Volume 1: Microwave Remote Sensing Fundamentals and Radiometry. Addison-Wesley Publishing Company, Reading, MA, 1981.

Walker, A.E. and B.E. Goodison. 1993. Discrimination of a wet snow cover using passive microwave data. Annals of Glaciology, 17:307-311.

Wang, J.R., R. Meneghini, H. Kumagai, T.T. Wilheit, W.C. Boncyk, P. Racette, J.R. Tesmer, and B. Maves. 1994. Airborne active and passive microwave observations of super typhoon Flo. IEEE Trans. Geoscience and Remote Sensing, 32:231-242.

# 17.3 Archive/DBMS Usage Documentation

None.

# 18. Glossary of Terms

None.

# 19. List of Acronyms

ASCII - American Standard Code for Information Interchange

BOREAS - BOReal Ecosystem-Atmosphere Study

BORIS - BOREAS Information System

CD-ROM - Compact Disk-Read-Only Memory

DAAC - Distributed Active Archive Center

EOS - Earth Observing System

EOSDIS - EOS Data and Information System FFC-W - Focused Field Campaign - Winter

FOV - Field of View

GIS - Geographic Information System

GMT - Greenwich Mean Time

GPS - Global Positioning System
GSFC - Goddard Space Flight Center
HTML - HyperText Markup Language

HYD - Hydrology

INS - Inertial Navigation System

IR - InfraRed

MTPE - Mission to Planet Earth

MW - MicroWave

NASA - National Aeronautics and Space Administration

NSA - Northern Study Area

NSIDC - National Snow and Ice Data Center
ORNL - Oak Ridge National Laboratory
PANP - Prince Albert National Park

PC - Personal Computer

PRT5 - Borneo Model PRT-5 radiation thermometer SMMR - Scanning Multichannel Microwave Radiometer

SSA - Southern Study Area

SSM/I - Special Sensor Microwave Imager

SWE - Snow Water Equivalent
URL - Uniform Resource Locator

#### 20. Document Information

#### **20.1 Document Revision Date**

Written: 23-Jan-1997 Revised: 26-Jul-1999

#### 20.2 Document Review Date

BORIS Review: 02-Jul-1998 Science Review: 06-Jul-1998

#### 20.3 Document ID

#### 20.4 Citation

When using these data, please include the following acknowledgment as well as citations of relevant papers in Section 17.2:

The microwave brightness temperature data set was intended to provide accurate measurements of thermal microwave radiation from snow fields. This data set was developed with support from NASA's Mission to Planet Earth (MTPE) BOREAS Project. Thanks are due to BORIS at GSFC for distributing the data and to Drs. Chang, Hall, and Foster of the Hydrological Sciences Branch, NASA GSFC, for producing these data products.

If using data from the BOREAS CD-ROM series, also reference the data as:

Chang, A.T.C., D.K. Hall, and J.L. Foster, "Validation of a Passive Microwave Snow Water Equivalent Algorithm Using an Energy Balance Model." In Collected Data of The Boreal Ecosystem-Atmosphere Study. Eds. J. Newcomer, D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers. CD-ROM. NASA, 2000.

#### Also, cite the BOREAS CD-ROM set as:

Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM. NASA, 2000.

#### 20.5 Document Curator

#### 20.6 Document URL

#### REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE July 2000	3. REPORT TYPE AND DATES COVERED Technical Memorandum	
4. TITLE AND SUBTITLE Technical Report Series on the Bo BOREAS HYD-2 Estimated Sno Measurements 6. AUTHOR(S)	•	• .	5. FUNDING NUMBERS  923 RTOP: 923-462-33-01
Hugh Powell and Alfred T.C. Forrest G. Hall and David E.	Knapp, Editors		
7. PERFORMING ORGANIZATION NAME Goddard Space Flight Center Greenbelt, Maryland 20771	E(S) AND ADDRESS (ES)		8. PEFORMING ORGANIZATION REPORT NUMBER  2000-03136-0
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS (ES)  National Aeronautics and Space Administration Washington, DC 20546-0001			10. SPONSORING / MONITORING AGENCY REPORT NUMBER  TM-2000-209891  Vol. 21
11. SUPPLEMENTARY NOTES			
Unclassified—Unlimited Subject Category: 43 Report available from the NASA 7121 Standard Drive, Hanover,	A Center for AeroSpace Info		12b. DISTRIBUTION CODE

#### 13. ABSTRACT (Maximum 200 words)

The surface meteorological data collected at the BOREAS tower and ancillary sites are being used as inputs to an energy balance model to monitor the amount of snow storage in the boreal forest region. The BOREAS HYD-2 team used SWE derived from an energy balance model and in situ observed SWE to compare the SWE inferred from airborne and spaceborne microwave data, and to assess the accuracy of microwave retrieval algorithms. The major external measurements that are needed are snowpack temperature profiles, in situ snow areal extent, and SWE data. The data in this data set were collected during February 1994 and cover portions of the SSA, NSA, and the transect areas. The data are available from BORIS as comma-delimited tabular ASCII files.

14. SUBJECT TERMS BOREAS, hydrology, snow water equivalent (SWE), microwave retrieval algorithms.			15. NUMBER OF PAGES 18 16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT $UL$